

REMARKS

This Preliminary Amendment cancels the original claims, without prejudice, in the underlying PCT Application No. PCT/DE2004/001627. The Preliminary Amendment also adds new claims 15-30. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE2004/001627 includes an International Search Report, dated November 19, 2004, a copy of which is submitted herewith.

Applicants assert that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON LLP

P. U. C. No. 41,727

Dated: 2/6/06

By: *GA*
Gerard A. Messina
Reg. No. 35,952

One Broadway
New York, NY 10004
(212) 425-7200

IMAGE RECORDING SYSTEM

~~Background Information~~ Field Of The Invention

The present invention relates to an image recording system and a method for producing an
5 image recording system.

~~DE~~ Background Information

German Published Patent Application No. 199 17 438-A1 describes a circuit configuration and
a method for producing a circuit configuration, the circuit configuration including a printed
circuit board and an image recorder disposed thereon. A lens holder for accommodating
10 and securing optical elements is also described. ~~DE~~ German Published Patent Application No.
199 17 438 A1 contains no references to an image recording system having a simple design,
accompanied at the same time by high accuracy of the image recording system.

~~Summary of the~~ Of The Invention

The image recording system described below, especially for use in a motor vehicle, made up of
15 at least one image sensor, at least one optical unit, at least one housing and fastening means for
fixing the image sensor in position relative to the housing – the housing having means for
accommodating the optical unit, the housing having alignment means on the inside that permit
an alignment, especially an attachment-free axial alignment, of the main axis of the image
sensor and the main axis of the optical unit relative to each other - has the advantage that a
20 simple design is achieved, accompanied at the same time by high accuracy of the image
recording system.

The housing means for accommodating the optical unit is advantageously a threaded mount. A
threaded mount offers many advantages. First of all, it is possible to mount the optical unit by
screwing it into the housing in simple and positionally-accurate fashion. Moreover, the
25 threaded mount offers the possibility of adjusting the image sharpness of the image sensor in a
simple manner by screwing the optical unit in or out.

It is particularly advantageous that the image sensor is arranged on a printed circuit board,
since this permits short signal paths and energy-supply paths to downstream electronics units.
This advantageously contributes to a compact design of the image recording system. It is also

advantageous if, in this context, the printed circuit board is able to be positioned relative to the housing by second alignment means, particularly at least with the aid of at least one spacer. High mechanical stability and high vibrational tolerance of the image recording system are thereby attained, which, because of this, is particularly suitable for use in automotive engineering, thus, for installation in a motor vehicle.

The use of a tension spring as fastening means for fixing the image sensor in position relative to the housing is advantageous, since tension springs as a releasable connection permit a simple mounting.

It is particularly advantageous that at least one part of the alignment means is adjustable, since it is thereby possible to compensate for tolerances in the production of the image sensor and/or the housing. In this connection, at least three spacers as first alignment means have proven to be advantageous for setting the image sensor apart from the housing, preferably at least two of the at least three spacers being adjustable in the spacing direction.

The method described in the following for producing an image recording system, in particular an image recording system ~~as recited in one of the preceding claims~~— in which an attachment-free, axial alignment of the main axis of an image sensor of the image recording system and the main axis of an optical unit of the image recording system relative to each other is implemented by alignment means mounted on the inner side of a housing of the image recording system, the main axis of the image sensor and the main axis of the optical unit are radially aligned relative to each other as a function of image data of the image sensor in such a way that the image sensor generates the image data from a test pattern located outside of the housing – has the advantage that high accuracy is achieved by the feedback mounting of the image sensor, i.e., the printed circuit board having the image sensor, relative to the optical unit or the housing. It is also advantageous that the image sharpness is set as a function of the image data from the test pattern by adjusting the position of the optical unit in the housing of the image recording system using an adjusting mechanism, since in so doing, both the alignment of the image sensor with respect to the optical unit and the image sharpness are set in one manufacturing process.

It is especially advantageous that, as a function of the image data from the test pattern, at least one adjustment parameter of the image sensor, e.g., at least one adjustment parameter for the intrinsic calibration and/or at least one adjustment parameter of the fixed pattern noise

correction is/are ascertained and optionally set, since in so doing, still another adjustment process is carried out in integrated fashion during the production of the image recording system. This advantageously leads to a reduction in manufacturing costs for the image recording system, which at the same time exhibits high accuracy.

- 5 The above-indicated advantages for the image recording system also hold true for a method for producing an image recording system according to the present invention.

~~Further advantages will become apparent from the following description of exemplary embodiments with reference to the figures, and from the dependent claims.~~

Brief Description of the Drawing

- 10 Hereinafter, ~~the present invention is explained in greater detail on the basis of the specific embodiments depicted in the drawing. The figures show:~~Fig. 1—Of The Drawings
Fig. 1 shows an image recording system of the preferred exemplary embodiment;
Fig. 2—2 shows a variant of the image recording system of the preferred exemplary embodiment;
15 ~~Fig. 3—~~*Fig. 3 shows* a flow chart of the method of the preferred exemplary embodiment;
Fig. 4 shows a further variant of the image recording system in a sectional view;
~~Fig. 5—~~*5 shows* another variant of the image recording system in a sectional view.

Detailed Description of the Exemplary Embodiments

- 20 In the following, an image recording system, particularly for use in a motor vehicle, and a method for producing an image recording system are described.

The image recording system includes an image sensor, an optical unit, a housing and fastening means for fixing the image sensor in position relative to the housing, the housing having alignment means on the inner side that permit an alignment, particularly an attachment-free, axial alignment, of the main axis of the image sensor and the main axis of the optical unit
25 relative to each other.

Image recording systems provided for automotive use must, on one hand, be very rugged, but all at once must also be very accurate. At the same time, another criterion is that the image recording systems be inexpensive. High accuracy of image recording systems may be attained,

for example, by an additional degree of complexity in the design, pins stop edges having highly precise dimensional accuracy representing the significant solution possibilities. The solution possibilities described are generally associated with increased costs. These costs are necessary for the assembly process, but not for the use of the image recording system.

5 In principle, feedback systems also make it possible to achieve the required accuracy. For example, it is conceivable to incorporate external sensors, e.g., position-reference sensors, into the production line when manufacturing the image recording system, which measure the image recording systems during production and intervene in controlling fashion in response to deviations. For instance, it is conceivable for these external sensors to monitor features on the
10 object to be produced which in the design, have a dimensionally true connection with the precision used, in that, for example, an imprinted circle is monitored that stands dimensionally true with respect to a sensor utilized later, particularly an image sensor. In this context, the useful signal is thus not evaluated, but rather a feature via an external sensor which, on its part, is produced in an imprecisely known dimensional accuracy with respect to the actual useful
15 sensor.

In the following, an image recording system and a method for producing an image recording system are described which make it possible to accomplish the feedback with the actual image sensor, no additional features on the object, thus, the image sensor, being necessary for production. Consequently, the manufacturing precision corresponds nearly exactly to the use
20 precision of the image sensor. A prerequisite for this is that the image recording system with the image sensor be at least partially functional in this production step. To that end, the image recording system is designed in such a way that it is possible to shift the printed circuit board together with the image sensor and subsequently secure it in the shifted state.

Figure 1 shows an image recording system of the preferred exemplary embodiment, made up of
25 a housing 2, an optical unit 1, an image sensor 12 (imager chip), spacers 4 and a tension spring 16. The image recording system is made up of an optical unit 1 and an imager 5 that is positioned with dimensional accuracy relative to this optical unit 1. In the preferred exemplary embodiment, optical unit 1 is designed as a cylinder screwed directly into housing 2 into a threaded cylindrical hole 3. In the preferred exemplary embodiment, three spacers 4 are
30 mounted on the inside of housing 2 around cylindrical hole 3 having optical unit 1. Three spacers 4 are a minimum number for establishing a plane. The plane thus established is nearly perpendicular to the axis of cylindrical hole 3, and therefore perpendicular to the main axis of

optical unit 1 located in cylindrical hole 3. This plane permits the axial alignment of the main axis of image sensor 12 and the main axis of optical unit 1 relative to each other. The main axis of image sensor 12 is the vertical onto the light-sensitive plane of image sensor 12 through the image center. The dimensional accuracy between the plane, defined by spacers 4, and the axis of cylindrical hole 3 is achievable, for example, by computer-aided manufacturing methods, e.g., by material processing on CNC milling machines. The axis of cylindrical hole 3 corresponds within given tolerances to the later optical axis of the image recording system, the direction of the optical axis of the image recording system being established through two points, the nodal point of the lens and the midpoint of image sensor 12. Image sensor 12 (imager chip) is positioned at the planes defined by spacers 4. Image sensor 12 contains imager 5, thus, the photosensitive part of image sensor 12, in housing 6 of image sensor 12, as well as a transparent protective cover 7 that is mounted in plane-parallel fashion with respect to imager 5. The dimensional accuracy of imager 5 in relation to protective cover 7 is accomplished with high quality in the chip production. On the other hand, the dimensional accuracy of electrical connections 8 on the bottom side of image sensor 12 and the position of image sensor 12 on printed circuit board 9 play no role for the necessary precision. Further spacers 10 are mounted at a greater distance to cylindrical hole 3 in relation to the dimensions of image sensor 12, these spacers 10 being produced and mounted with less precision compared to spacers 4 in the area of cylindrical hole 3. Located on printed circuit board 9 are the functional electronics and a socket 11 for the transmission of data, e.g., image data, and energy, so that printed circuit board 9 together with image sensor 12 can be driven. To mount image sensor 12, using an x-y traversing table 13 having printed-circuit-board receptacles 17, image sensor 12 with protective cover 7 on printed circuit board 9 is pressed against middle spacers 4. A positioning motor 14 turns optical unit 1 into cylindrical hole 3 until the electronics via socket 11 emit a sharp image. The x-y traversing table 13 is alternatively controlled manually by operating personnel and/or automatically, until features on test pattern 15, which are located at a defined location in front of optical unit 1, move to the desired position within the image, generated by image sensor 12, in the form of image data. In an alternative variant, the process of focusing and the x-y alignment are repeated iteratively until the desired precision is achieved. During or immediately after the adjustment process described, in one variant of the preferred exemplary embodiment, further adjustment parameters of the image quality of image sensor 12 are determined. In particular, they include at least one adjustment parameter for the intrinsic calibration and/or at least one adjustment parameter of the fixed pattern noise correction. After the desired positioning is accomplished, printed circuit board 9 is pressed via a tension spring

16 against housing 2, so that the image sensor chip is no longer able to move relative to
cylindrical hole 3. Alternatively or additionally, an adhesive agent and/or at least one
screw-connection means are possible for fixing image sensor 12 in position relative to housing
2. In conclusion, reverse-side cover 20 is mounted, for example, by screws. This reverse-side
5 cover 20 has the function to clamp printed circuit board 9 and/or to achieve the electromagnetic
compatibility (EMC) imperviousness by grounded connection, and/or to attain a thermal
junction between image sensor 12 and the surroundings for cooling image sensor 12.

Figure 2 shows a variant of the image recording system of the preferred exemplary
embodiment, only the central part of Figure 1 having image sensor 12 and optical unit 1 being
10 depicted. Components already specified in Figure 1 are no longer clarified in the following.

The high dimensional accuracy of imager 5 with respect to protective cover 7 on image sensor
12 increases the costs for producing image sensor 12. Therefore, in the variant of the preferred
exemplary embodiment described here, compensation is made for the wobble angle error, thus
the rotation of image sensor 12 about the x axis and/or y axis, between imager 5 and protective
15 cover 7 using a suitable adjusting mechanism. To that end, at least two of the at least three
spacers used are replaced by screws 21 in this variant of the preferred exemplary embodiment.

During the focusing process via positioning motor 14, at the same time at least two further
screw positioning motors 19 are driven, accompanied by measurement of features distributed
over the image, imager 5 in image sensor 12 being set in alignment with optical unit 1. Figure 3
20 shows a flow chart of the method for producing an image recording system of the preferred
exemplary embodiment, including the variants described. In first method step 30, the image
sensor together with the protective cover on the printed circuit board is pressed against the
spacers that are located in the region of the cylindrical hole and, in the variant described here,
are implemented as screws. In second method step 31, the optical unit is screwed by a
25 positioning motor into the cylindrical hole, until a downstream evaluation unit emits a signal
that a sharp image is present. Subsequent method step 32 is used to radially align the main axis
of the image sensor and the main axis of the optical unit relative to each other by bringing the
image sensor to the desired x-y position via an x-y traversing table. In subsequent method step
33, the main axis of the image sensor and the main axis of the optical unit are axially aligned
30 relative to each other by adjustment of the screws. Optionally, method steps 31, 32, 33 are
repeated iteratively until the desired alignment precision is attained. In subsequent method step
34, as a function of the image data from the test pattern, at least one further adjustment
parameter of the image sensor, e.g., at least one adjustment parameter for the intrinsic

calibration and/or at least one adjustment parameter of the fixed pattern noise correction, is ascertained and optionally set. Last method step 36 is used to fix the image sensor in position relative to the housing using fastening means.

In the following, another advantageous embodiment variant of the invention is elucidated with reference to Figure 4 and Figure 5.

Image recording system 40 shown in Figure 4 includes a housing 40.1, 44 made up of an essentially cup-shaped housing member 40.1 and a cover 44 sealing housing member 40.1. An optical module 41 is joined to housing member 40.1. Disposed in housing member 40.1 is an image sensor 47 that has an imager chip 42 and is in operative connection with optical module 41. In this context, operative connection means that optical module 41 images an image, corresponding to the receiving region of optical module 41, onto image sensor 47, or, more precisely, onto imager chip 42 of image sensor 47. Image sensor 47, together with imager chip 42 made of photosensitive silicon, is preferably bonded and/or soldered to a first printed circuit board 48. Printed circuit board 48 bearing image sensor 47 is arranged on a first surface of an intermediate support 49. Intermediate support 49 bears a second printed circuit board 40.2 on its second surface. Disposed on this second printed circuit board are electronic components, plug connectors and the like (not shown in the figure), which are electrically connected from the standpoint of circuit engineering to image sensor 47 situated on first printed circuit board 48. At least partial areas of the periphery of intermediate support 49 have the shape of a spherical lateral surface. The regions of the periphery of intermediate support 49 thus shaped engage with form locking in correspondingly form-matched regions 43 of the inside wall of housing member 40.1, which thus likewise represent parts of a spherical surface. Intermediate support 49 is therefore virtually supported in a kind of spherical joint. In a first embodiment variant, at least two partial areas of the periphery of the intermediate support defining the diameter of intermediate support 49 are shaped in such a way in the form of a spherical surface and engage in at least two form-matched regions 43 of the inside wall of housing member 40.1. In another embodiment variant, three such areas are provided that are expediently arranged in rotationally symmetrical fashion, and therefore are set apart from each other angle-wise by approximately 120°. In a further embodiment variant, four partial areas may be provided which are set apart from each other angle-wise by 90°. In another embodiment variant which permits particularly secure mounting of the intermediate support, the complete periphery of intermediate support 49 is circular and formed as part of a spherical lateral surface supported in

a form-matched annular structure in the interior of housing member 40.1. In all the embodiment variants described above, intermediate support 49 is mounted by way of the bearing similar to a ball bearing in housing member 40.1 in a manner allowing easy rotation and tilting. In this way, by turning and/or tilting intermediate support 49, imager chip 42 can be aligned very easily and nevertheless with high precision with optical module 41. After setting the optimum alignment position, intermediate support 49 may be permanently fixed in position in its ball bearing by, for example, a quick—hardening adhesive, in order to secure the alignment position.

In the embodiment variant of an image recording system 50 shown in Figure 5, three adjusting screws 51 are provided that are rotationally mounted in housing bottom 44. These adjusting screws 51 are preferably arranged symmetrically with respect to the optical axis of image recording system 50, and viewed angle-wise, for instance, are uniformly spaced apart on a circle in such a way that they have an angular spacing of 120° . The tips of adjusting screws 51 either engage directly with the outer surface of printed circuit board 40.2 facing them, or, in an embodiment variant, engage through openings in printed circuit board 40.2 directly with the outer surface of intermediate support 49 facing them. Therefore, these adjusting screws 51 form a three-point support adjustment for the precise adjustment of intermediate support 49 into a specific tilt position. When a tilt position of intermediate support 49 corresponding to an optimal alignment is achieved by twisting adjusting screws 51, the three adjusting screws 51 are expediently secured in their position by an adhesive.

An image recording system according to Figure 4 is expediently produced as follows. Optical module 41, sealed frontally by a protective cover 45 transparent to radiation, is joined to housing member 40.1 of the housing with the aid of a joining means 46, in particular an adhesive. Printed circuit boards 40.2, 48, fitted with the components such as image sensor, electronic components, plug connections and the like, are joined, in particular screwed, to intermediate support 49. An adhesive, preferably able to be cured by UV radiation, is applied on regions 43 of housing member 40.1 that have the shape of a spherical lateral surface. With image sensor 47 aligned in the direction of optical module 41, the intermediate support is subsequently introduced into housing member 40.1 and supported there in the "ball bearing" formed by regions 43. Image sensor 47 is adjusted with respect to optical module 41 by turning and tilting intermediate support 49 within the ball bearing. After reaching an optimal alignment

position, the adhesive is cured by irradiation with UV light. Intermediate support 49 is thereby permanently fixed in position. In conclusion, cover 44 is bonded to housing member 40.1.

The method for manufacturing an image recording system according to Figure 5 differs from the method previously described only in that the tilt position of intermediate support 49 is
5 precisely adjusted by adjusting screws 51.

The image recording systems described and the method for producing an image recording system are suitable for CCD image sensors and/or CMOS image sensors.

Abstract Of The Disclosure

An image recording system, particularly for use in a motor vehicle, and a method for producing an image recording system are provided. The image recording system includes an image sensor (12), an optical unit (1), a housing (2) and fastening means arrangement for fixing the image sensor (12) in position relative to the housing (2), permit axial alignment of the main axis of the image sensor (12) and the main axis of the optical unit (1) relative to each other.

(Figure 1)